



Target Monitoring Quick Guide

www.supertargetsystems.com

Rev 7

Wireless Target Trailing Camera System TTC-100

Our NEW wireless target trailing camera system is a TRUE Plug & Play version and it works out of the box with no setup required. It has been designed for quick deployment in the field.

The system allows easy positioning of the camera in any shooting situation. Every system comes with camera, display, rechargeable batteries, and their chargers.



Introduction

This camera system is a very effective, low cost and ideal solution designed for target monitoring using wireless technology, battery operated camera, high resolution display and 11 inches Adjustable Friction Power Articulating Magic Arm. This is a plug-and-play system working out of the box with very minimum or no setup required.

Features

- Digital wireless 2.4GHz camera
- 7-inch high resolution TFT digital LED display
- Digital wireless long range transmission
- Storage to TF card
- Support up to 32 GB TF card

Camera

- Sensor Type: Color CMOS
- Resolution: 640x480(VGA)
- Lens Focus: 3.6mm
- Viewing Angle: 92
- Lens Size: 1/4"
- Transmission Frequency: 1sm2400-2483MHz
- Transmission Power: 23dBm
- Modulation Type: GFSK
- Transmission Range: 100m-300m
- Power Supply: DC 5V
- Power Consumption: Daytime:300mA Night:700mA
- Operating Temperature: -10° C~+60° C
- Camera Size: 100mm x 58mm x 58mm

Monitor

- LCD: 7"TFT
- LCD Resolution: 800x480
- Receiving Frequency: ISM2400-2483MHz
- Modulation Type: GFSK
- Receiving Sensitivity: <80dBm
- Battery Type: Lithium Battery
- Battery Capacity: 1020mAh
- Video Output: 1.0Vpp
- Video Format: NTSC/PAL
- Storage Type: TF Card
- Card Maximum Capacity: 32GB
- Power Supply: DC 5V
- Power Consumption: 1320ma(charge)
- Dimensions: 187(L)*130(W)*20(H)mm
- Operating Temperature: -10 C~+60 C

System Setup

1. Make sure the batteries are fully charged using the included chargers
2. Mount the camera on the included 11 inches Adjustable Friction Power Articulating Magic Arm
3. Mount the entire assembly either on the target carrier or on the carrier deflector's arm
4. Connect the antennas
5. Turn the camera ON by switching the battery ON
6. The more free space around the display and around the camera the stronger the signal

Kit Includes:

- Digital Wireless Camera
- 7-inch Digital Wireless Receiver
- Lithium Battery for Receiver
- Adapter for Camera
- Adapter for Receiver
- Antenna
- Video Cable
- USB Cable
- Lithium battery for camera



Thank You for your business!

Tel: (800) 556-3162 | Sales: sales@supertargetsystems.com

Technical Support: support@supertargetsystems.com

2055 Comprehensive Dr. | Aurora, IL - 60505