



HD Target Monitoring Quick Guide

Our NEW tripod version system is a TRUE Plug & Play version, and it works out of the box with no setup required. It has been designed for quick deployment in the field.

The tripod system allows easy positioning of the camera AND/OR the Yagi antenna (used for 1000yd or more distances) in any shooting situation. Every system comes with:

1. Camera with its own battery pack and tripod
2. Display with its own battery pack and sun protection guard that can also be used as a stand
3. USB charging cables
4. The 1000yd or more systems come with an external antenna and its own tripod
5. Case



System Setup

1. Make sure the batteries are fully charged using the included chargers (2-3hours)
2. Mount the camera on the included tripod
3. Mount the display on its own stand
4. Connect the antennas (antennas sizes will differ depending the system ordered)
5. Plug in the USB connectors of the display and camera in their respective batteries
6. Turn the camera ON by switching the battery ON
7. Turn the monitor ON by switching the battery ON and by pressing the monitor's ON button
8. Once connectivity is ensured, take the camera and the display to the target area and position the camera such that it is not in the line of fire while the image on the display is clear enough to see your shots (3-5 ft away at about 45 degrees)
9. Walk back to the shooting position while monitoring the display to ensure the connectivity is not lost
10. The strength of the wireless signal will depend greatly on any obstructions: trees, hills, buildings, fences etc.
11. The more free space around the display and around the camera the stronger the signal